JakMatDairy

THE SOLUTION TO RACE PROBLEM AREAS CAUSED BY HIGH STOCK TRAFFIC

Stabilise race pressure points and create a smooth transition zone from race to concrete with the JakMat*Dairy* system.

Enjoy the long term benefits:

- Enhanced drainage no potholes& less carry-over to shed
- Reduced risk of lameness
- Improved cow flow
- Lower maintenance cost & effort
- Ultimate strength & material retention due to the unique honeycomb structure

For more information visit www.jakmat.co.nz



JakMatDairy

The race stabilisation mat for high pressure animal traffic areas

Easy installation & maintenance with the JakMatDairy system:

- Easy to handle, lay & cut to size if needed.
- Lay between milking with few disruptions.
- Lower on-going maintenance costs due to a long lasting and stable race surface being created.
- Reduce mud and excrement 'carry over' into the milking shed with reduced clean down
- Holds soft aggregates, sympathetic to animals hooves, on race surface thereby reducing material refill cost.

Product Features:

- Unique interlocking system between mats giving even weight distribution over cells.
- Designed with a honeycomb structure which, as in nature, is inherently strong.
- NZ designed and manufactured for local conditions especially high rainfall.
- Produced from 100% recycled plastic with UV stabilisation for long life.
- Stackable and light weight for lower transportation and storage costs.

View real-life installations online at www.youtube.com/jakmatnz



TECHNICAL DATA	
Mat Size	Mat 585 x 400 x 43
Weight Bearing (Compression Testing)	Test: JakMat packed with GAP 7 aggregate and compacted by hand. A 200mm x 9mm carbons steel plate disc was loaded as follows:
	1. Loaded to 3500kg/34.4KN - No Visual Change Observed
	2. Loaded to 12910kg/126.6KN - 0.7 mm deflection Observed
Material	Polyolefin (Recycled) UV stabilised
Colour	Black
Coverage	4.27 mats / sq metres
No. Mats/Pallet	192 units (45 sq metres coverage)
Pallet Dimensions	1.2 x 1.2 x 0.92 metres
Pallet Weight	243kg*
Pallet & Strapping Material	Wood pallet PP plastic strapping
v = 11	

^{*} Pallet weight can be changed to suit transportation particularly where helicopter transportation will be used.





and compact

Lay 25-50 mm layer of same aggregate as § to bring up to surrounding edges

Jakaar Industries Ltd
66 Cryers Rd, Highbrook, Manukau 2013 PO Box 204069
Highbrook, Manukau 2161, Auckland, New Zealand
Tel +64 9 273 5511, Fax +64 9 273 5512
Email sales@jakaar.co.nz





